

VITLAB® UV-protect volumetric flasks, PMP, Class A with NS stoppers, PP



UV-absorbing, highly transparent. For storage of light-sensitive substances.

With ring mark individually calibrated to 'In'.

Class A tolerances according to DIN EN ISO 1042.

With printed lot number and batch certificate.

Thermal stress up to 121 °C (autoclaving) does not permanently exceed the tolerance limit.

To preserve markings, cleaning at no higher than 60 °C is recommended.

Also available with DAkkS calibration certificate or individual quality certificate (at additional cost).

More information on VITLAB® UV-protect can be found on page 124.

| Volume ml | Tolerance ± ml | Height* mm | Neck NS | PU | Cat. No. |
|-----------|----------------|------------|---------|----|----------|
| 10 | 0.04 | 90 | 10/19 | 2 | 670950 |
| 25 | 0.04 | 115 | 10/19 | 2 | 671950 |
| 50 | 0.06 | 150 | 12/21 | 2 | 672950 |
| 100 | 0.10 | 180 | 14/23 | 2 | 673950 |
| 250 | 0.15 | 235 | 19/26 | 2 | 674950 |
| 500 | 0.25 | 270 | 19/26 | 2 | 675950 |
| 1000 | 0.40 | 310 | 24/29 | 1 | 676950 |

* Height without stopper



VITLAB® UV-protect replaces brown glass and is...

- ... substantially lighter in weight
- ... practically unbreakable
- ... practically impermeable in the UV region
- ... comparable to a light protection factor of 20

Volumetric flasks, PMP, Class A with NS stoppers, PP



Highly transparent.

With ring mark individually calibrated to 'In'.

Class A tolerances according to DIN EN ISO 1042.

With printed lot number and batch certificate.

Thermal stress up to 121 °C (autoclaving) does not permanently exceed the tolerance limit.

To preserve markings, cleaning at no higher than 60 °C is recommended.

Also available with DAkkS calibration certificate or individual quality certificate (at additional cost).

| Volume ml | Tolerance ± ml | Height* mm | Neck NS | PU | Cat. No. |
|-----------|----------------|------------|---------|----|----------|
| 10 | 0.04 | 90 | 10/19 | 2 | 67704 |
| 25 | 0.04 | 115 | 10/19 | 2 | 67104 |
| 50 | 0.06 | 150 | 12/21 | 2 | 67204 |
| 100 | 0.10 | 180 | 14/23 | 2 | 67304 |
| 250 | 0.15 | 235 | 19/26 | 2 | 67404 |
| 500 | 0.25 | 270 | 19/26 | 2 | 67504 |
| 1000 | 0.40 | 310 | 24/29 | 1 | 67604 |

* Height without stopper

