Volumetric flasks, PP, Class B with NS stoppers, PP

Highly transparent.
With ring mark individually calibrated to 'In'.
Class B tolerances according to DIN EN ISO 1042.
Thermal stress up to 60 °C does not permanently exceed the tolerance limits.
To preserve markings, cleaning at no higher than 60 °C is recommended.

Volume ml	Tolerance ± ml	Height* mm	Neck NS	PU	Cat. No.
10	0.08	90	10/19	2	677941
25	0.08	115	10/19	2	671941
50	0.12	150	12/21	2	672941
100	0.20	180	14/23	2	673941
250	0.30	235	19/26	2	674941
500	0.50	270	19/26	2	675941
1000	0.80	310	24/29	1	676941

* Height without stopper

Volumetric flasks, PP, Class B, with screw cap, PP

Highly transparent.
With ring mark individually calibrated to 'In'.
Class B tolerances according to DIN EN ISO 1042.
Thermal stress up to 60 °C does not permanently exceed the tolerance limits.
To preserve markings, cleaning at no higher than 60 °C is recommended.

Volume ml	Tolerance ± ml	Height* mm	Thread GL	PU	Cat. No.
10	0.08	90	18	2	677891
25	0.08	115	18	2	671891
50	0.12	150	18	2	672891
100	0.20	180	18	2	673891
250	0.30	235	25	2	674891
500	0.50	270	25	2	675891
1000	0.80	310	32	1	676891

* Height without screw cap