

PRODUCT CATALOG



Scaling new heights in Research
DLAB your accessible solution





TC2000-G1/G2/G3 Thermal Cycler Gradient

Application

TC2000-G1/G2/G3 is an indispensable laboratory instrument in the field of molecular biology, which can be used for gene sequencing, gene cloning, gene expression, mutation, and plays an important role in various fields such as agriculture, food testing, environmental science, drug development and so on.

Features

- » 10-inch large screen new UI interface, divided into single-channel / dual-channel / three-channel, to meet different experimental requirements
- » With advanced gradient temperature control technology, high-performance and long-lasting Peltier refrigeration and heating, which can achieve precise temperature control in zones.
- » Multi-channel module design, can run several different PCR gradient programs at the same time, to achieve multi-purpose machine
- » Self-adaptive pressure lever hot cap, close and tighten the cap in one step, can be adapted to different heights of test tubes
- » Supports up to 199 cycles to perform the next operation, and runs a countdown disc to visually display the remaining time
- » Edge temperature compensation technology for good temperature uniformity and gradient settings for easy optimisation of experimental conditions
- » Real-time display of the running status of the programme, you can set the security account and password according to customer demand
- » Automatic power failure protection, automatically execute unfinished cycles after power restoration to ensure the safe operation of the whole amplification process.
- » Hot lid temperature and hot lid operating mode can be set to meet different experimental application requirements
- » USB interface, support for U-disk storage/reading PCR data, support for U-disk software update, can be customised to meet the function of multiple file storage, support for Touch down PCR and Long PCR experiments
- » Compatible with common 0.2mL PCR tubes, PCR-8Strips and 96-well PCR plates (no skirt, full skirt, half skirt)



Application Areas



Medical Research

For pathogen detection, e.g. gene identification of viruses, bacteria and fungi, mutation analysis of disease-associated genes, gene expression analysis in cancer research, etc.



Biological Research

Genotyping, gene cloning, species identification, evolutionary analyses, and other studies



Forensic Science

DNA analysis of crime scene samples to help identify suspects and provide a basis for public security case detection



Agricultural sector

For genetic research on crops and livestock, e.g. breed improvement, genetic disease detection, etc.



Food testing

Detection of pathogenic bacteria, genetically modified ingredients in food, etc.



Environmental Science

Analysing microbial communities in the environment and detecting genetic effects of pollutants on organisms



Drug Development

Screening of drug targets, assessment of drug effects on gene expression



Genetic studies

Conducting diagnosis and research on human genetic diseases



Palaeontology

Analyses species identification and classification, development and evolution, extinction event studies and the origin of species in ancient organisms

Specifications

Model	TC2000-G1	TC2000-G2	TC2000-G3
Sample Capacity	96×0.2mL PCR tube 12×PCR-8strips 96 PCR Microplate	96×0.2mL PCR tube 12×PCR-8strips	
Module	1×96	2×48	3×32
Heating Temp.Range/°C	0-105		
Lid Temperature Range /°C	30-115		
Temperature Display/°C	0.1		
Temp Control Accuracy/°C	±0.1		
Temp Uniformity@55°C	±0.2		
Max.Heating/Cooling Rate	5°C/Sec		
Gradient Temp Setting Range/°C	30-105		
Gradient Range	1-42°C, enter 0 to turn off the gradient	1-25°C, enter 0 to turn off the gradient	
Temperature Control Method	Block/Tube		
Adapter Block Material	Aluminum		
Display	10.1inch LCD 1280×800		
Input	Touch panel		
Power off protect	Yes		
Skip to the next step	Yes		
Communication Interface	USB2.0、WIFI		
Number of Program Stores	20000+ (USB FLASH)		
User Defined File System	Up to 30 steps and 199 cycles in a single program		
Power Supply	100-240V,50/60HZ 600W	100-240V,50/60HZ 1000W	100-240V,50/60HZ 1500W
Dimensions [L×W×H]	422×310×264mm	422×310×261mm	422×310×252mm
Weight	11Kg	11Kg	13Kg
Permissible Ambient Temperature and Humidity	5-40°C,80%RH		



DLAB SCIENTIFIC CO.,LTD.

Add: YuAn Road 31,Beijing Airport Economic Core Zone,Shunyi District,Beijing101318,China

Tel: 86-10-85653451/52/53, 60498800

Fax: 86-10-85653383

E-mail: info@dlabsci.com

Service: service@dlabsci.com

Service Hotline: 400-1100-556

Web: www.dlabsci.com