Recommended reagents

Below is a list of suitable reagents to work with bottle top dispenser

Acetaldehyde
Acetic acid (glacial), 100%
Acetic acid, ≤ 96%
Acetic anhydride
Acetone
Acetonitrile
Acetophenone
Acetyl chloride
Acetylacetone
Acrylonitrile
Acrylic acid
Adipic acid
Ally alcohol
Aluminium chloride
Aminoacids
Ammonia, ≤ 20%
Ammonia, 20-30%
Ammoniu chloride
Ammonium fluoride
Ammonium sulfate
n-Amyl acetate
Amyl alcohol (pentanol)
Amyl chloride (chloropentane)
Aniline
Barium chloride
Benzal dehyde
Benzene (Benzol)
Benzine (Petroleum benzine) bp 70-180ºC
Benzoyl chloride
Benzyl alcohol
Benzylamine
Benzylchloride
Boric acid, ≤ 10%
Bromobenzene
Bromonaphtalene
Butanediol
1-Butanol
n-Butyl acetate
Butyl methyl ether
Butylamine
Butyric acid
Calcium carbonate
Calcium chloride
Calcium hydroxide
Calcium hypochlorite
Carbon tetrachloride
Chloro naphthalene
Chloroacetaldehyde, ≤ 45%
Chloroacetic acid
Chloroacetone
Chlorobenzene
Chlorobutane
Chloroform
Chlorosulfonic acid
Chromic acid, ≤ 50%
Chromosulfuric acid
Copper sulfate
Cresol
Cumene (Isopropyl benzene)
Cyclohexane
Cyclohexanone
Cyclopentane
Decane
1-Decanol
Dibenzyl ether
Dichloroacetic acid
Dichlorobenzene
Dichloroethane
Dichloroethylene
Dichloromethane
Diesel oil (Heating oil),
bp 250-350 °C
Diethanolamine
Diethyl ether
Diethylamine
1.2 Diethylbenzene
Diethylene glycol
Dimethyl sulfoxide (DMSO)
Dimethylaniline
Dimethylformamide (DMF)
1.4 Dioxane
Diphenyl ether
Essential oil
Ethanol
Ethanolamine
Ethyl acetate
Ethylbenzene
Ethylene chloride
Fluoroacetic acid
Formaldehyde, ≤ 40%
Formamide
Formic acid, ≤ 100%
Glycerol
Glycol (Ethylene glycol)
Glycolic acid, ≤ 50%
Heating oil (Diesel oil),
bp 250-350 °C
Heptane
Hexane
Hexanoic acid
Hexanol
Hydriodic acid, ≤ 57%
Hydrobromic acid
Hydrochloric acid, ≤ 20%
Hydrochloric acid, 20-37%
Hydrogen peroxide,≤ 35%
Isoamyl alcohol
Isobutanol
Isooctane
Isopropanol (2-Propanol)
Isopropyl ether
Lactic acid
Methanol
Methoxybenzene
Methyl benzoate
Methyl butyl ether
Methyl ethyl ketone
Methyl formate
Methyl propyl ketone
Methylene chloride
Mineral oil (Engine oil)
Monochloroacetic acid
Nitric acid, ≤ 30%
Nitrobenzene
Oleic acid
Oxalic acid
n-Pentane
Peracetic acid
Perchloric acid
Perchloroethylene
Petroleum, bp 180-220 °C
Petroleum ether, bp 40-70 °C
Phenol
Phenylethanol
Phenylhydrazine
Phosphoric acid, ≤ 85%
Phosphoric acid, 85%
Sulfuric acid, 98% 1:1
Piperidine
Potassium chloride
Potassium dichromate
Potassium hydroxide
Potassium permanganate
Propionic acid
Propylene glycol (Propanediol)
Pyridine
Pyruvic acid
Salicylaldehyde
Scintilation fluid
Silver acetate
Silver nitrate
Sodium acetate
Sodium chloride
Sodium dichromate
Sodium fluoride
Sodium hydroxide, ≤ 30%
Sodium hypochlorite
Sulfuric acid, ≤ 98%
Tartaric acid
Tetrachloroethylene
Tetramethylammonium hydroxide
Toluene
Trichloroacetic acid
Trichlorobenzene
Trichloroethane
Trichloroethylene
Trichlorotrifluoro ethane
Triethanolamine
Triethylene glycol
Trifluoro ethane
Trifluoroacetic acid (TFA)
Turpentine
Urea
Xylene
Zinc chloride, ≤ 10%
Zinc sulfate, ≤ 10%