MX-S+

Digital Vortex Mixer

Features

- LCD screen displays real-time speed and time for easy adjustment and monitoring.
- Adjustable speed ranges from gentle to vigorous mixing to suit various needs.
- Stable with pressure-mounted accessories to prevent slippage and splashing.
- Brushless DC motor for high stability and maintenance-free operation.
- Sturdy base ensures stability during operation for safety.
- Includes various accessories for different sizes and types of tubes and plates.
- Low noise for a quiet working environment.

Specifications	MX-S+
Speed	100-3000 rpm
Display	LCD
Amplitude	4 mm
Operating Modes	Touch, Continuous
Time Range	1 s - 99 min 59 s
Motor Type	Brushless DC Motor
Dimensions (L×W×H)	160x146x115mm
Weight	3.4kg
Power Supply	100-240 V, 50/60 Hz
Input Voltage	24 V
Power Consumption	25 W
Ambient Temperature & Humidity	5-40°C, 80% RH
Enclosure Protection	IP21

VT2.3 Universal top plate,Ø100mm

VT2.6 Snap-in Universal top plate,Ø85mm

VT2.5 Erlenmeyer flask attachment(100mL-250m

PS2.1 & PS2.2Microplate clamp

VT2.4 Ampule/Tube Attachment

VT2.7.4-VT2.7.6 Horizontal Plastic Clamp

Accessories of Vortex Mixer MX-S+ & MX-Pro

Accessories of MX-S+&MX-Pro

VT2.3 Cat. No.18901365

Universal top plate，compatible with VT1.3.1-VT1.3.12 Tube Adapter

VT2.4 Cat. No.18901366

Ampule/Tube Attachment，4pc ampule/tube（0.2mL-15mL）

VT2.5 Cat. No.18901367

Erlenmeyer flask attachment (100mL-250mL)，Operating speed: 0~1500rpm

PS2.1 Cat. No.18901360

Microplate clamp，Suitable for workboards (full skirt PCR plates, cell culture plates, enzyme-linked immunosorbent assay plates, deep well plates, etc. Half skirt/no skirt PCR plates need to be used with rectangular foam, which is already included)

Accessories of MX-S+&MX-Pro （New）

VT2.1 Cat. No.18901379

Top cup，Suitable for MX-Pro

VT2.1 Cat. No.18901380

Top cup，Suitable for MX-S+

VT2.2 Cat. No.18901373

Flat Rubber Sleeve (Standard)

VT2.6 Cat. No.18901368

Snap-in Universal top plate，compatible withVT2.6.1-VT2.6.5 Tube Adapter

VT2.6.1 Cat. No.18901378

Tube Adapter，25 holes, Ø4.5mm(0.1-0.5mL)，Applicable to RUN mode

VT2.6.2 Cat. No.18901377

Tube Adapter，21 holes, Ø8mm(1.5-2mL)，Applicable to RUN mode

VT2.6.3 Cat. No.18901376

Tube Adapter，16 holes, Ø10mm(2-5mL，Not compatible with 5 mL conical tubes. Compatible with standard 5 mL centrifuge tubes.)，Applicable to RUN mode

VT2.6.4 Cat. No.18901375

Tube Adapter，8 holes, Ø14mm (10-15mL，supports 5 mL conical tubes; incompatible with standard 5 mL centrifuge tubes.)，Applicable to RUN mode

VT2.6.5 Cat. No.18901374

Tube Adapter，4 holes, Ø25.5mm(50mL)，Applicable to RUN mode

VT 2.7.4 Cat. No.18901870

Horizontal Plastic Clamp，24 holes×1.5mL Test Tube (Circular plate)

VT 2.7.5 Cat. No.18901871

Horizontal Plastic Clamp，12 holes×15mL Test Tube (Circular plate)

VT 2.7.6 Cat. No.18901872

Horizontal Plastic Clamp，6 holes×50mL Test Tube (Circular plate)

PS2.2 Cat. No.18901361

Snap-in Microplate clamp,Suitable for workboards (full skirt PCR plates, cell culture plates, enzyme-linked immunosorbent assay plates, deep well plates, etc. Half skirt/no skirt PCR plates need to be used with rectangular foam, which is already included)

*Material color may vary slightly during the initial launch phase. Please refer to the actual product.